

The perfect boats to fulfill all your needs



SP 176 FNP SE


SPECIFICATIONS	Center line	Beam	Chine width	Max. depth	Approx. draft	Transom height	Approx. weight	NMMA (USA) / Transport Canada				ALUMINUM THICKNESS		BUILT-IN GAS TANK (w/ in-dash gauge)
								Max. H.P. cap.	Max. weight cap.	Max. weight person cap.	Max. person cap.	Bottom	Side	
SP 176 FNP SE	5.3 m (17'-5")	2.3 m (92")	1.9 m (75")	1.0 m (40")	0.8 m (30")	0.6 m (25")	590 kg (1301 lb.)	86 kW (115 H.P.)	747 kg (1647 lb.)	411 kg (907 lb.)	** 7 [5]	2.5 mm (.100")	1.8 mm (.072")	132 L (35 U.S. gal.)
SP 176 FNP	5.3 m (17'-5")	2.3 m (92")	1.9 m (75")	1.0 m (40")	0.8 m (30")	0.6 m (25")	588 kg (1296 lb.)	86 kW (115 H.P.)	747 kg (1647 lb.)	411 kg (907 lb.)	** 7 [5]	2.5 mm (.100")	1.8 mm (.072")	132 L (35 U.S. gal.)

** Max. person cap.: NMMA [Transport Canada]

For a complete list of standard and optional equipment, see pages 48-51. Photomontages show various features and options. Some accessories shown may not be available on all models.

Super Pro 176 SE & 176

Fish 'n Promenade



SP 176 FNP SE SP 176 FNP

- livewell
- storage compartment
- rod storage /organizer
- ice chest

SP 176 FNP SE



SP 176 FNP

/ KEY STANDARD FEATURES

- Deep Vee reverse chine hull design
- 75" of chine width & 25" transom
- Bow dual SportFlo™ aerated livewell system
- No-FeedBack™ steering system w/ tilt wheel
- Lowrance® X-50 DS fish/depth finder w/ swivel bracket
- Walk-thru tinted curved tempered glass windshield w/ door
- Upholstered bow coaming pads w/ bow cushions
- 2 deluxe pedestal folding fishing seats
- 2 stern jump seats
- Port side sleeper seat
- 7-foot lockable rod storage
- AM/FM/CD Stereo w/ iPod & Sirius Satellite Compatible
- 12 or 24V bow trolling motor panel

/ for Special Edition version only

- Dark beige metallic paint w/ black accent color
- Sliding rails for captain's chair
- Stern boarding ladder



1. Lowrance® X-50 DS fish/depth finder on swiveling bracket 2. Optional ski pylon 3. SportFlo™ electric-fill aerated bow livewell 64 L (17 U.S. gal.) with overflow, thru-hull drain and anti-spill cover 4. AM/FM/CD Stereo with iPod controls and Sirius Satellite Compatible 5. 2 fold-down stern jump seats that can be converted to a casting platform 6. Port side sleeper seat 7. Complete fully-lit instrumentation

Enjoy your weekends on a **Princecraft**




55 174

SPECIFICATIONS	Center line	Beam	Chine width	Max. depth	Approx. draft	Transom height	Approx. weight	NMMA (USA) / Transport Canada				ALUMINUM THICKNESS		BUILT-IN GAS TANK (w/ in-dash gauge)
								Max. H.P. cap.	Max. weight cap.	Max. weight person cap.	Max. person cap.	Bottom	Side	
55 174	5.3 m (17'-5")	2.3 m (92")	1.9 m (75")	1.0 m (40")	0.8 m (30")	0.6 m (25")	585 kg (1289 lb.)	86 kW (115 H.P.)	747 kg (1647 lb.)	411 kg (907 lb.)	** 7 [5]	2.5 mm (.100")	1.8 mm (.072")	132 L (35 U.S. gal.)
55 172	5.3 m (17'-5")	2.3 m (92")	1.9 m (75")	1.0 m (39")	0.8 m (30")	0.6 m (25")	556 kg (1225 lb.)	86 kW (115 H.P.)	712 kg (1570 lb.)	376 kg (830 lb.)	** 6 [5]	2.5 mm (.100")	1.8 mm (.072")	132 L (35 U.S. gal.)
55 164	5.0 m (16'-6")	2.1 m (84")	1.8 m (69")	0.9 m (35")	0.8 m (31")	0.5 m (20")	457 kg (1008 lb.)	56 kW (75 H.P.)	640 kg (1410 lb.)	386 kg (850 lb.)	** 6 [5]	2.3 mm (.090")	1.8 mm (.072")	77 L (20 U.S. gal.)

** Max. person cap.: NMMA [Transport Canada]

For a complete list of standard and optional equipment, see pages 48-51. Photomontages show various features and options. Some accessories shown may not be available on all models.

Super Sport 174, 172 & 164



SS 174



SS 172



SS 164

- livewell
- storage compartment
- rod storage /organizer
- ice chest

SS 174



SS 172

SS 164

KEY STANDARD FEATURES

- Deep Vee reverse chine hull design
- 25" transom (SS 172 and SS 174 only)
- Deep self draining splashwell
- Stainless steel bow and stern eyes
- 4 chromed cleats
- Raised bow casting platform w/ removable deck (SS 164 & SS 174 only)
- Raised aft casting platform w/ 2 jump seats (SS 164 & SS 174 only)
- Rear flip deck convert bench (SS 172 only)
- Electric-fill aerated SportFlo™ livewell system (2 in SS 172)
- 7-foot lockable rod storage
- Bow trolling motor attachment
- 2 pedestal folding fishing seats
- Walk-thru tinted curved tempered glass windshield w/ door
- Electrical system w/ breaker protection
- Electric bilge pump
- Built-in floor fuel system



1. Rear flip deck convert bench (on SS 172 only) 2. Helm console with complete fully-lit instrumentation and optional Lowrance® X-50 DS fish/depth finder on swiveling bracket (on SS 164 & SS 174) 3. SportFlo™ electric-fill aerated stern livewell 64 L (17 U.S. gal.) with overflow, thru-hull drain, removable minnow bucket and anti-spill cover (N/A on SS 164) 4. Optional stand-up high canvas with aluminum frame 5. Optional coaming pads and bow seat cushions 6. Holding handles





FROM DAWN 'TIL DUSK.

If you're fortunate enough to chase fish from sun-up until sundown, your boat should have all the features and comfort to make your time worthwhile. The Pro Series includes more fishing extras that any other boat in its class, exceeding even your most rigorous demands. With the Pro Series, you can make it an all-day affair.



1. 7-foot lockable side rod storage* 2. Optional coaming pads and bow seat cushions* 3. AM/FM/CD Stereo with iPod controls and Sirius Satellite Compatible* 4. 2 fold-down stern jump seats that can be converted to a casting platform*

* On some models

Serious fish boats



PRO 206


SPECIFICATIONS	Center line	Beam	Chine width	Max. depth	Approx. draft	Transom height	Approx. weight	NMMA (USA) / MANUFACTURER'S RECOMMENDATIONS				ALUMINUM THICKNESS		BUILT-IN GAS TANK (w/ in-dash gauge)
								Max. H.P. cap.	Max. weight cap.	Max. weight person cap.	Max. person cap.	Bottom	Side	
PRO 207	6.1 m (20'-0")	2.5 m (100")	2.1 m (84")	1.3 m (50")	0.9 m (34")	0.6 m (25")	826 kg (1820 lb.)	168 kW (225 H.P.)	1002 kg (2209 lb.)	612 kg (1350 lb.)	10	2.8 mm (.110")	1.8 mm (.072")	227 L (60 U.S. gal.)
PRO 206	6.1 m (20'-0")	2.5 m (99")	2.1 m (84")	1.2 m (48")	0.9 m (34")	0.6 m (25")	821 kg (1810 lb.)	168 kW (225 H.P.)	1002 kg (2209 lb.)	612 kg (1350 lb.)	10	2.8 mm (.110")	1.8 mm (.072")	227 L (60 U.S. gal.)

For a complete list of standard and optional equipment, see pages 48-51. Photomontages show various features and options. Some accessories shown may not be available on all models.

Pro 207 & 206



PRO 206



PRO 207

PRO 206

- livewell
- storage compartment
- rod storage /organizer
- ice chest



PRO 207

/ KEY STANDARD FEATURES

- Deep Vee double reverse chine hull design
- 84" of chine width & 25" transom
- Deep self draining splashwell
- 4 stainless steel cleats
- Raised bow casting platform w/ removable deck
- Raised aft casting platform w/ privacy enclosure and optional toilet (Pro 207 only)
- Bow & stern dual ProFlo™ aerated livewell system
- Walk-thru tinted curved tempered glass windshield w/ door
- Lowrance® X-52 fish/depth finder w/ swivel bracket
- 3 deluxe pedestal folding fishing seats
- 2 stern jump seats
- Built-in floor lockable rod organizer (12 rods)
- Complete fully-lit instrumentation
- AM/FM/CD Stereo w/ iPod & Sirius Satellite Compatible
- 12 or 24V bow trolling motor panel w/ voltmeter & tilt switch
- No-FeedBack™ steering system w/ dual cables
- Electrical system w/ breaker protection
- Automatic bilge pump

1. Lockable side panel storage **2.** Optional coaming pads and bow seat cushions **3.** Optional downrigger supports **4.** Lowrance® X-52 fish/depth finder on swiveling bracket **5.** Open storage under the casting platform **6.** ProFlo™ electric-fill aerated stern livewell 129 L (34 U.S. gal.)* with timer, recirculation, overflow, thru-hull drain, light and anti-spill cover (on Pro 206)

* 64 L (17 U.S. gal.) on Pro 207 with a removable minnow bucket

Boats for **all-day fishability** and **all-day comfort**



PRO 176

SPECIFICATIONS	Center line	Beam	Chine width	Max. depth	Approx. draft	Transom height	Approx. weight	NMMA (USA) / Transport Canada				ALUMINUM THICKNESS		BUILT-IN GAS TANK (w/ in-dash gauge)
								Max. H.P. cap.	Max. weight cap.	Max. weight person cap.	Max. person cap.	Bottom	Side	
PRO 186	5.6 m (18'-6")	2.4 m (95")	2.0 m (80")	1.2 m (46")	0.8 m (33")	0.6 m (25")	676 kg (1490 lb.)	131 kW (175 H.P.)	863 kg (1902 lb.)	525 kg (1158 lb.)	** 8 [7]	2.8 mm (.110")	1.8 mm (.072")	151 L (40 U.S. gal.)
PRO 176	5.3 m (17'-6")	2.3 m (92")	2.0 m (80")	1.0 m (41")	0.8 m (31")	0.6 m (25")	635 kg (1400 lb.)	112 kW (150 H.P.)	787 kg (1736 lb.)	450 kg (992 lb.)	** 7 [6]	2.8 mm (.110")	1.8 mm (.072")	151 L (40 U.S. gal.)

** Max. person cap.: NMMA [Transport Canada]

For a complete list of standard and optional equipment, see pages 48-51. Photomontages show various features and options. Some accessories shown may not be available on all models.


Pro 186 & 176



PRO 186



PRO 186



PRO 176

- livewell
- storage compartment
- rod storage /organizer
- ice chest



PRO 186

/ KEY STANDARD FEATURES

- Deep Vee double reverse chine hull design
- 80" of chine width & 25" transom
- Deep self draining splashwell
- 4 stainless steel cleats
- Raised bow casting platform w/ removable deck
- Raised aft casting platform w/ storage
- Bow & stern dual ProFlo™ aerated livewell system
- Walk-thru tinted curved tempered glass windshield w/ door
- Lowrance® X-52 fish/depth finder w/ swivel bracket
- 2 deluxe pedestal folding fishing seats
- 2 stern jump seats
- Built-in floor lockable rod organizer (6 rods)
- Complete fully-lit instrumentation
- AM/FM/CD Stereo w/ iPod & Sirius Satellite Compatible
- 12 or 24V bow trolling motor panel w/ voltmeter & tilt switch
- No-FeedBack™ steering system w/ dual cables
- Electrical system w/ breaker protection
- Automatic bilge pump



1. ProFlo™ electric-fill aerated stern livewell 64 L (17 U.S. gal.) with timer, recirculation, overflow, thru-hull drain, removable minnow bucket, light and anti-spill cover
2. Optional vinyl floor covering and snap-in carpet **3.** Lowrance® X-52 fish/depth finder on swiveling bracket **4.** Holding handles **5.** 2 fold-down stern jump seats that can be converted to a casting platform **6.** Lockable in-floor 6-rod organizer

Built to take **on big water**




PRO 185 GL

SPECIFICATIONS	Center line	Beam	Chine width	Max. depth	Approx. draft	Transom height	Approx. weight	NMMA (USA) / Transport Canada				ALUMINUM THICKNESS		BUILT-IN GAS TANK (w/ in-dash gauge)
								Max. H.P. cap.	Max. weight cap.	Max. weight person cap.	Max. person cap.	Bottom	Side	
PRO 185 GL	5.6 m (18'-6")	2.4 m (95")	2.0 m (80")	1.2 m (46")	0.8 m (33")	0.6 m (25")	658 kg (1450 lb.)	131 kW (175 H.P.)	863 kg (1902 lb.)	525 kg (1158 lb.)	6	2.8 mm (.110")	1.8 mm (.072")	151 L (40 U.S. gal.)

For a complete list of standard and optional equipment, see pages 48-51. Photomontages show various features and options. Some accessories shown may not be available on all models.

Pro 185 GL



PRO 185 GL

- livewell
- storage compartment
- rod storage /organizer
- ice chest

PRO 185 GL



PRO 185 GL

/ KEY STANDARD FEATURES

- Deep Vee double reverse chine hull design
- 80" of chine width & 25" transom
- Deep self draining splashwell
- 4 stainless steel cleats
- Raised bow casting platform w/ storage
- Bow dual ProFlo™ aerated livewell system
- Insulated stern fish box w/ cutting board
- Walk-thru tinted curved tempered glass windshield w/ door
- Lowrance® X-52 fish/depth finder w/ swivel bracket
- 2 deluxe pedestal folding fishing seats
- Lockable built-in floor storage
- Sides and stern rod holders
- Complete fully-lit instrumentation
- AM/FM/CD Stereo w/ iPod & Sirius Satellite Compatible
- 12 or 24V bow trolling motor attachment
- No-FeedBack™ steering system w/ dual cables
- Electrical system w/ breaker protection
- Automatic bilge pump



1. Optional wash down system 2. Lowrance® X-52 fish/depth finder on swiveling bracket 3. ProFlo™ electric-fill aerated bow livewell 77 L (20 U.S. gal.) with timer, recirculation, overflow, thru-hull drain, removable minnow bucket, light and anti-spill cover 4. Stern area with easy access to livewell and downriggers 5. Deep self draining splashwell

It's as easy to drive as
it is **exciting to fish from**



PRO 179 WS

SPECIFICATIONS	Center line	Beam	Chine width	Max. depth	Approx. draft	Transom height	Approx. weight	NMMA (USA) / Transport Canada				ALUMINUM THICKNESS		BUILT-IN GAS TANK (w/ in-dash gauge)
								Max. H.P. cap.	Max. weight cap.	Max. weight person cap.	Max. person cap.	Bottom	Side	
PRO 179 WS	5.3 m (17'-4")	2.3 m (92")	2.0 m (80")	0.9 m (37")	0.8 m (31")	0.6 m (25")	589 kg (1299 lb.)	101 kW (135 H.P.)	640 kg (1410 lb.)	304 kg (670 lb.)	** 5 [4]	2.5 mm (.100")	1.8 mm (.072")	151 L (40 U.S. gal.)
PRO 179 SC	5.3 m (17'-4")	2.3 m (92")	2.0 m (80")	0.9 m (37")	0.8 m (31")	0.6 m (25")	557 kg (1229 lb.)	101 kW (135 H.P.)	640 kg (1410 lb.)	304 kg (670 lb.)	** 5 [4]	2.5 mm (.100")	1.8 mm (.072")	151 L (40 U.S. gal.)


** Max. person cap.: NMMA [Transport Canada]

For a complete list of standard and optional equipment, see pages 48-51. Photomontages show various features and options. Some accessories shown may not be available on all models.

Pro 179 WS & 179 SC



PRO 179 SC



PRO 179 WS



PRO 179 SC

- livewell
- storage compartment
- rod storage /organizer



PRO 179 SC

/ KEY STANDARD FEATURES

- Deep Vee reverse chine hull design
- 80" of chine width & 25" transom
- 4 chromed cleats
- Raised bow & aft casting platforms w/ storage
- Bow & stern dual SportFlo™ aerated livewell system
- Lowrance® X-52 fish/depth finder w/ swivel bracket
- 2 deluxe pedestal folding fishing seats
- Built-in floor lockable rod organizer (6 rods)
- Complete fully-lit instrumentation
- 12 or 24V bow trolling motor panel
- Built-in floor fuel system
- Electrical system w/ breaker protection

/ WS only

- Rotomolded twin consoles w/ dash panel and switches
- Walk-thru tinted curved tempered glass windshield w/ door

/ SC only

- Rotomolded side console w/ dash panel and switches
- Smoked windscreen w/ quick release



1. Lowrance® X-52 fish/depth finder on swiveling bracket 2. Optional dowrigger supports 3. SportFlo™ electric-fill aerated stern livewell 77 L (20 U.S. gal.) with overflow, thru-hull drain, removable minnow bucket and anti-spill cover 4. Helm console with complete fully-lit instrumentation and Lowrance® X-52 fish/depth finder on swiveling bracket 5. Twin consoles with walk-thru tinted curved tempered glass windshield with door (on WS only) 6. Lockable in-floor 6-rod organizer

Boats with as much fight as the fish you chase

PRO 169 SC

SPECIFICATIONS	Center line	Beam	Chine width	Max. depth	Approx. draft	Transom height	Approx. weight	NMMA (USA) / Transport Canada				ALUMINUM THICKNESS		BUILT-IN GAS TANK (w/ in-dash gauge)
								Max. H.P. cap.	Max. weight cap.	Max. weight person cap.	Max. person cap.	Bottom	Side	
PRO 169 WS	4.9 m (16'-2")	2.2 m (87")	1.8 m (71")	0.9 m (35")	0.8 m (33")	0.5 m (20")	448 kg (987 lb.)	67 kW (90 H.P.)	553 kg (1220 lb.)	280 kg (618 lb.)	** 5 [3]	2.3 mm (.090")	1.8 mm (.072")	106 L (28 U.S. gal.)
PRO 169 SC	4.9 m (16'-2")	2.2 m (87")	1.8 m (71")	0.9 m (35")	0.8 m (33")	0.5 m (20")	420 kg (925 lb.)	67 kW (90 H.P.)	553 kg (1220 lb.)	280 kg (618 lb.)	** 5 [3]	2.3 mm (.090")	1.8 mm (.072")	106 L (28 U.S. gal.)

** Max. person cap.: NMMA [Transport Canada]

For a complete list of standard and optional equipment, see pages 48-51. Photomontages show various features and options. Some accessories shown may not be available on all models.

Pro 169 WS & 169 SC



PRO 169 SC



PRO 169 WS



PRO 169 SC

- livewell
- storage compartment
- rod storage /organizer



PRO 169 WS

/ KEY STANDARD FEATURES

- Reverse chine hull design
- 71" of chine width & 20" transom
- 4 chromed cleats
- Raised bow and aft casting platforms w/ storage
- Bow & stern SportFlo™ aerated livewell system
- Lowrance® X-52 fish/depth finder w/ swivel bracket
- 2 deluxe pedestal folding fishing seats
- Complete fully-lit instrumentation
- 7-foot lockable rod storage
- 12 or 24V bow trolling motor panel
- Electric bilge pump
- Built-in floor fuel system

/ WS only

- Rotomolded twin consoles w/ dash panel and switches
- Walk-thru tinted curved tempered glass windshield w/ door

/ SC only

- Rotomolded side console w/ dash panel and switches
- Smoked windscreen w/ quick release



1. 7-foot lockable rod storage 2. 12 or 24 V bow trolling motor panel and receptacle 3. Lowrance® X-52 fish/depth finder on swiveling bracket
 4. Helm console with complete fully-lit instrumentation and Lowrance® X-52 fish/depth finder on swiveling bracket 5. Open storage under the bow platform
 6. Deep self draining splashwell

For anglers **on the go**



PRO 165 SC

SPECIFICATIONS	Center line	Beam	Chine width	Max. depth	Approx. draft	Transom height	Approx. weight	NMMA (USA) / Transport Canada				ALUMINUM THICKNESS		BUILT-IN GAS TANK (w/ in-dash gauge)
								Max. H.P. cap.	Max. weight cap.	Max. weight person cap.	Max. person cap.	Bottom	Side	
PRO 165 SC	4.9 m (16'-2")	2.2 m (87")	1.8 m (71")	0.8 m (33")	0.7 m (29")	0.5 m (20")	406 kg (895 lb.)	56 kW (75 H.P.)	554 kg (1221 lb.)	300 kg (661 lb.)	** 5 [4]	2.3 mm (.090")	1.8 mm (.072")	106 L (28 U.S. gal.)
PRO 169 BT	4.9 m (16'-2")	2.2 m (87")	1.8 m (71")	0.8 m (33")	0.7 m (29")	0.5 m (20")	354 kg (780 lb.)	45 kW (60 H.P.)	527 kg (1162 lb.)	300 kg (661 lb.)	** 5 [4]	2.3 mm (.090")	1.8 mm (.072")	106 L (28 U.S. gal.)

** Max. person cap.: NMMA [Transport Canada]

For a complete list of standard and optional equipment, see pages 48-51. Photomontages show various features and options. Some accessories shown may not be available on all models.


Pro 165 SC & 169 BT




Pro 165 SC
only



PRO 165 SC



PRO 165 SC



PRO 169 BT

- livewell
- storage compartment
- rod storage /organizer



PRO 169 BT

/ KEY STANDARD FEATURES

- Reverse chine hull design
- 71" of chine width & 20" transom
- Bow SportFlo™ aerated livewell system
- 2 deluxe pedestal folding fishing seats
- Complete fully-lit instrumentation
- 7-foot lockable rod storage
- Electrical system w/ breaker protection
- Electric bilge pump
- Built-in floor fuel system
- 12 or 24V bow trolling motor panel

/ Pro 169 BT only

- Stern side mount dash panel w/ switches
- Raised bow casting platform w/ storage

/ Pro 165 SC only

- Rotomolded side console w/ dash panel and switches
- Smoked windscreen w/ quick release
- Raised bow and aft casting platforms w/ storage

1. SportFlo™ electric-fill aerated bow livewell 86 L (23 U.S.gal.)* with overflow, thru-hull drain and anti-spill cover (Pro 165 SC) **2.** 12 or 24V bow trolling motor panel and receptacle **3.** Deep cycle battery storage in bow area **4.** Optional Lowrance® X-50 DS fish/depth finder on swiveling bracket **5.** Helm console with complete fully-lit instrumentation and optional Lowrance® X-50 DS fish/depth finder on swiveling bracket (on Pro 165 SC only) **6.** Deluxe pedestal folding fishing seats (2)

* 77 L (20 U.S. gal.) on Pro 169 BT